

Logitank Klassic LTKL 100

A self bunded and transportable KLASSIC tank for the safe storage and handling of diesel and oils.

Ideal for refuelling vehicles, machinery, equipment and fleet.



Pictured with optional dispensing kit and lighting

Features

- Self bunded double wall design
- Fluid level dipstick for tank and interstitial space
- Vent pipe for tank and interstitial space
- Suction foot valve, overfill protection and electronic overfill alarm
- Corner container lock castings for ease of transport
- Access manway
- Warranty – 5 years structural, 1 year on valves; conditions apply

Options include:

- Inspection ladder
- Clip-on pump bay
- Multiple compartments
- Dispensing and fuel management

Tank Specifications

Description	
Safe Fill, litres	93,583 (95%)
Length, mm	14,630
Width, mm	2,438
Height, mm	3,200
Tare Weight, kg	18,600
Vent Pipe	Standard
Fluid Level Dipstick	Standard
Compliance	AS1940, AS1692, UL142, HSW (Haz. Sub.) Reg 2017



Suitable for bulk fuel farm applications

Information and photographs are for marketing purposes only and are considered accurate at time of publication. Actual product may differ to images shown due to continual improvement processes, design changes and optional extras. V3417

AUTHORISED DISTRIBUTOR OF

