

Specification Sheet

Description **Fuelchief DC25**

Part No **TA-2500**



The baby in the DC Slimline series family. The DC25 is excellent for smaller operations or as a back-up tank for generators and pumps. The DC25 tank also has the key and unique features of 110% secondary containment and the full height internal pump cabinet. Below are some of the key features of this slim line tank:

- ✦ 2,370L model with large secure cabinet to house all pumps and equipment
- ✦ Full height access door with 3-way locking system and anti-theft design for extra security
- ✦ Hempel C4-H Marine grade paint system
- ✦ Spill sump in cabinet base to contain spillage
- ✦ Improved inner tank design with no internal bracing for safe servicing
- ✦ Sloped floor in inner tank for better water catchment and recovery
- ✦ Water inspection and suction port housed under lockable hatch
- ✦ Large access manhole for maintenance and inspection of inner tank
- ✦ Extra feed and return ports for running auxiliary equipment
- ✦ Lockable fill point with integrated dipstick
- ✦ Base of tank sealed in an anti-rust underseal

Ext Dimensions (w,d,h)	Capacity (total)	Capacity (safe fill)
1160 x 2530 x 1752mm	2,500L	2,370L
Design Approval Cert	Design Standard	Weight (empty)
100111-00016142	AS1692	910kg