

# Logitank Blue LTBL 60

## Specifications



### Description

Diesel Safe Fill, litres	54,000
AdBlue®, AUS32, DEF Safe Fill, litres	7,000
Length, mm	12,192
Width, mm	2,438
Height, mm	2,896
Tare Weight, kg	16,713
Vent Pipe	Standard
Fluid Level Dipstick	Standard
Compliance	AS1940, AS1692, AS1657, UL142



A self-bunded tank for the safe storage and handling of both diesel and AdBlue®, AUS32 or other DEF products from the one unit.

Ideal for refuelling commercial vehicles that use AdBlue®, AUS32 or DEF.



Dual Diesel and insulated DEF chemical resistant tanks

- Self-bunded dual compartment design
- Bunded pump bay with lockable weatherproof doors
- Fill and dispense points in the main lockable pump bay
- Galvanised access ladder and platform
- Corner container lock castings for ease of transport
- Access manways
- Warranty – 5 years structural, 1 year on valves

#### Diesel tank standard with:

- Fluid level dipsticks for tank and interstitial space
- Vent pipe for diesel tank and interstitial space
- Suction foot valve, overfill protection and electronic overfill alarm

#### DEF tank standard with:

- Chemical resistant vented tank
- Insulated tank and dispensing line for temperature control
- Submerged stainless steel pump
- Stainless steel pipework
- Fluid level dipsticks for tank and interstitial space

AUTHORISED DISTRIBUTOR



[www.logitank.com.au](http://www.logitank.com.au)



[www.petrotec.co.nz](http://www.petrotec.co.nz) | p: 0800 477 134  
105B Hayton Road | Wigram  
PO Box 10125 | Phillipstown | Christchurch

Information and photographs are for marketing purposes only and are considered accurate at time of publication.

Actual product may differ to images shown due to continual improvement processes, design changes and optional extras. V1\_Petrotec; Released 0616