

# Logitank Classic LTKL 68



## Specifications

### Description

Safe Fill, litres	64,600
Length, mm	12,192
Width, mm	2,438
Height, mm	2,896
Tare Weight, kg	14,100
Vent Pipe	Standard
Fluid Level Dipstick	Standard
Compliance	AS1940, AS1692, UL142, HSNOCOP 24



A self bunded and transportable KLASSIC tank for the safe storage and handling of diesel and oils.

Ideal for refuelling vehicles, machinery, equipment and fleet.



*Pictured with optional dispensing package*

- Self bunded double wall design
- Fluid level dipstick for tank and interstitial space
- Vent pipe for tank and interstitial space
- Anti-syphon valve, overfill protection and electronic overfill alarm
- Corner container lock castings for ease of transport
- Access manway
- Option of different colours
- Warranty – 5 years structural, 1 year on valves; conditions apply

Pump bay model standard with:

- Bunded pump bay with lockable weatherproof doors
- Galvanised access ladder and platform; with ladder fitted to either side of the platform (ex-factory)
- Galvanised kick plate and middle rail provided for additional safety of users

AUTHORISED DISTRIBUTOR



[www.logitank.com.au](http://www.logitank.com.au)



[www.petrotec.co.nz](http://www.petrotec.co.nz) | p: 0800 477 134  
105B Hayton Road | Wigram  
PO Box 10125 | Phillipstown | Christchurch

Information and photographs are for marketing purposes only and are considered accurate at time of publication.

Actual product may differ to images shown due to continual improvement processes, design changes and optional extras. V2B\_Petrotec; Released 0616