

## Logitank

## Approvals:

- Complies to HSNOCOP:2004;
- AS1692:2006;
- AS1940:2004;
- AS1657:2013;

## Specifications:

- Single compartment, double skinned tank on a 10', 20', 40' or 48' ISO footprint;
- Lockable pump bund (LTKL12, 30, 68 and 80 tanks);
- Optional lockable remote pump bund (LTKL20, 38, 75 and 100 tanks);
- Galvanised foldable ladder and platform (AS1657 compliant) for access to dip points etc. (LTKL12, 30, 68 and 80 tanks). Ladder can be located on either side of tank;
- 3" overfill protection valve (1,500 lpm flow rate to 95% SFL);
- 2" anti-syphon valve;
- Internal ladder for access;
- Calibrated dipstick;
- · Interstitial dipstick;
- Interstitial space vented;
- Three 600mm dia. access manways and internal ladder (except LSK10, LTKL12 & 20);
- 3" camlock male hose filler with dust cap connection (except LSK10);
- Internal pipe work;
- Emergency vent;
- Roof sits above the side rails of the tank to stop water pooling;
- Inner and outer tanks all 6mm steel;
- Sandblasted to SA2.5;
- Underside of the tank base bitumen coated;
- Paint coating to C5-1 harsh environment standard with three coats Hempel paint to 240 micron thickness. Standard colour is grey (other colours available);
- Tank manufacture and compliance plates;
- 5 year structural warranty, one year values. Conditions apply;

Model No.	Safe Fill Level @ 95%		Tare Weight		
	(litres)	Length (m)	Width (m)	Height (m)	(Kg's)
				_	
LSK10	9,500	6.058	2.438	1.295	4,443
LTKL12	11,115	2,991	2.438	2.896	4.910
LTKL20	17,156	2.991	2.438	2.896	4,748
LTKL30	28,750	6.058	2.438	2.896	7,934
LTKL38	35,250	6.058	2.438	2.896	8,037





LTKL68	64,600	12.192	2.438	2.896	14,100
LTKL75	70,550	12.192	2.438	2.896	14,082
LTKL80	77,425	14.630	2.438	2.896	17,100
LTKL100	96,049	14.630	2.438	3.200	18,000
LTKL110	110,000	14,630	2,438	3.200	19,082

## **Accessories:**

- Electronic overfill alarm;
- Remote pump bund (for LTKL20, 38, 75, 100 & 110tanks);
- Access platform (for LTKL20, 38, 75, 100 & 110 tanks);
- High rise pylons and counter weights;
- Skid (LTKL12, 30 and 68 only);
- Tank cradles;

0916



